Grok
Light is life.

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit

Tubs 900mm

00-6001-05-M1

Nahtrang Design





TECHNICAL FEATURES

IP20



Power (W) : 36W

Total power consumption of light (W) : 41W

Real lumens : 1990

Real lm/W : 49

Colour temperature : LED warm-white 3000K

Lens / reflector angle : HORIZONTAL 124º

Structure material : Aluminium

Structure finish : Metallic black

Diffuser material : Methacrylate

Diffuser finish : Opal

Useful life : 50.000h L80B20

Equipment included : Yes, electronic

Brand : HEP

Voltage / frequency : 100-277V/50-60Hz

Warranty : 5 Years

Max. temperature : 25ºC

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED

Luminance C0º65º: 1177

Luminance 90º65º: 1034

CRI: 80

MacAdam steps: 5

Photobiological risk: RG0

UGR

UGR crosswise: 18.4

UGR lengthwise: 17.1

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	18.4
UGR lengthwise	17.1





LOGISTICS

Net weight (kg): 3.72

Packaged weight (kg): 7.48

Packaging: 960mm x 675mm x 315mm

1 Un

LIGHT APPLICATION